

[Technical Information]

Polymol FZU1 Liquid

Gujarat Polysol Chemicals Pvt. Ltd.

Plot no.-1734, 3rd Phase, G.I.D.C, Vapi(Gujarat)-INDIA
Tel-091-0260-2426407, Web: www.gujaratpolysol.com

❖ **Polymol FZU1 Liquid is an excellent dispersant and used in the production of Agro pesticide formulation. Polymol FZU1 Liquid is suitable for use in production of VAT and Disperse dyes at high temperature.**

Nature: Benzene sulphonic acid, 4-Hydroxy-, Polymer with formaldehyde & sodium sulphite condensate.

CAS No.: 71608-04-7

Specification:

Appearance	:	Reddish brown viscous liquid.
pH value (As such)	:	9.5 to 10.5
Solubility	:	Readily soluble in water
Solid	:	45 ± 1 %
Specific gravity	:	1.235 to 1.255
Viscosity@28°C (In B4 cup)	:	250 to 300 second

Properties: Very powerful dispersing agent with high molecular weight. Stabilizer, dispersing agent and precipitant for the chemical and allied industries. Dispersing agent and auxiliary for processing and polymerizing natural and synthetic rubber lattices & dispersing agent.

Storage: Product is alkaline in nature. Therefore it must be stored in its original sealed packaging. If stored properly in its original sealed packaging the shelf life is at least 12 months.

This information is based on our present state of knowledge and its intended to provide general notes on our products and their uses. It should not therefore be constructed as guaranteeing specific properties of the products described on suitability for particular application.

[Technical Information]

Polymol FZU1 Liquid

Gujarat Polysol Chemicals Pvt. Ltd.

Plot no.-1734, 3rd Phase, G.I.D.C, Vapi(Gujarat)-INDIA
Tel-091-0260-2426407, Web: www.gujaratpolysol.com

Safety: We know of no ill effects that could have resulted from using Polymol FZU1 Liquid for the purpose for which it is intended and from processing it in accordance with the current practice. According to the experience we have gained up to now and other information at our disposal, Polymol FZU1 Liquid does not exert any harmful effects on health, provided that it is used properly, due attention is given to the precautions necessary for handling chemicals, and the information and advice given in our Safety.

Labeling: Refer to latest Safety Data Sheet for detailed information on product safety.

Packing: Polymol FZU Liquid is available in 100 kgs HDPE drum & 250 kgs HDPE drum. Alternative packing sizes may be available upon request.

Pollution reducing & Environment friendly.

This information is based on our present state of knowledge and its intended to provide general notes on our products and their uses. It should not therefore be constructed as guaranteeing specific properties of the products described on suitability for particular application.